



"Model 1200"™

The tremendous capacity of the Dyna-Fog 1200 makes it the world leader in large scale fogging applications. The vast amount of fog covers large areas in a fraction of the time required by other equipment.

Everything you need to fight Malaria, Dengue, Encephalitis and other mosquito transmitted diseases.

The same dependable applicator that has provided years of reliable service now features an 11 HP Honda Engine and a 25% larger heater tank capacity.

Fully equipped with remote control operation, the machine can be totally operated from the cab of the vehicle. An hour meter, temperature and pressure gauges, two 120 volt AC receptacles, indicator lights and a 12 Volt Heavy Duty battery all are standard equipment on the "Model 1200".



The Ultimate Fog Applicator for Large Area Insect Control.

Besides being able to produce large amounts of fog, the "Model 1200" is one of the quietest fog generators in the world. Normal operation produces approximately 75 decibals (dba) of noise. This is a sound level quieter than most garden tractors.

When fitted with the optional ULV Attachment, the machine can be converted from a "Thermal Fogger" to a "Cold Fogger" in a matter of seconds.



High Volume Centrifugal Blower

Corrosion Resistant Stainless Steel Combustion Chamber

11 HP Honda Engine Electric Start, Overhead Valve

120 Volt AC Generator

Heavy Duty 12 Volt DC Battery Not Shown

Full Function Remote Control Box With Indicator Lights

Large Capacity, Corrosion Resistant Heater Tank

Adjustable Nozzle

Dyna-Fog® Quality

Removeable Remote Control Box Features In-Cab Visual/Operating Capabilities For...



- **Remote Start**
- **Analog Temperature Gauge**
- **Controllable Output**
- **Heating Chamber On/Off**
- **Fog On/Off**
- **Fog Rate-Low/High with Indicator Light**
- **Machine On/Off**
- **Accumulative Hour Meter**

SPECIFICATIONS

Thermal Fog Output	15-120 Gal/Hr	57-454 Liter/Hr
ULV Output	0-17 Gal/hr.	0-65 Lit/hr.
Weight (empty)	467 lbs.	211.8 kg.
Weight (full)	620 lbs.	281 kg.
Length (w/nozzle)	79 in.	199 cm.
Length (w/o nozzle)	55 in.	139 cm.
Width	35 in.	13.8 cm.
Height	32 in.	12.6 cm.
Gasoline Engine	11 HP Honda, Overhead Valve	
Burner Tank Capacity	15 Gal.	56.8 Liters
ULV DROPLET SIZE 10	- 140 MICRONS	
Fog Particle Size	10-100 Microns	

Shipping Data:

L x W x H	60 x 43 x 42 (in)	152 x 109 x 107 (cm)
Weight	585 lbs.	265.36 kg.
Volume	62.71 cu. ft.	1.77 cu. m.

FEATURES

- 120 Gal/hr. (454 Lit/hr.)- enables fogging 3 times faster than conventional vehicle mounted foggers. Large capacity is capable of covering 12 acres/min. (49,000 sq. m./min).
- ULV Pumping System 0-17 Gal/hr. (0-65 Lit/hr.)
- Powered by an 11 HP OHV Honda Engine
- 20 ft. (6.1 m) remote control cable with quick disconnect
- Adjustable fog output- DRY to WET fog- 15-120 Gal/hr. (57-454 Lit/hr.)
- Oil powered heater for reliable service
- Uses Kerosene, Diesel Fuel or the same #2 Fuel Oil for complete fogging operation.
- Complete remote control capability with instant Temperature and Hour reading
- Two 120 Volt AC receptacles for connecting work lights, etc...
- Safe- No dangerous Propane or formulation drum pressure
- No special tools required to operate
- One year limited warranty



P.O. Box 297
17335 US 31 North
Westfield, In 46060 USA
www.dynafog.com

Dyna-Fog and Model 1200 are registered trademarks or trademarks of Curtis Dyna-Fog, Ltd.