

Typhoon 2P

Powered by your choice of a 9 or 11 HP heavy duty OHV engine, the **TYPHOONT 2P** offers the features and quality components that have made **DYNA-FOG®** equipment the industry standard for Professional Mosquito Control.

The full featured Control Panel with Stainless Steel Flow Meter can be mounted within operator's reach to monitor Formulation Flow, Tank Pressure and Spray ON/OFF.

A night light makes viewing the control panel easy at any time. The large capacity Stainless Steel Formulation tank provides safe and dependable containment of chemical. Its compact size (66 cm" x 91 cm" base frame) enables the **TYPHOONT2P** be mounted on a small truck bed.

Built to rigid quality standards and backed by more than fifty years experience in the international spraying and fogging industry, the **DYNA-FOG® TYPHOONT2P** has proven to be an essential part of any spraying program where performance, simplicity and reliability are required.

All components are backed by Curtis Dyna-Fog's two-year limited warranty and Life-time Engine Ignition System warranty.



Specifications for the TYPHOONT2P

Vehicle Mounted ULV Applicator

Model:	2986-9 (9 HP version Briggs & Stratton) 2986-11 (11 HP version Honda)
Fuel Consumption:	2 liter/hour
Engine:	Available with 9 HP or 11 HP @ 4,000 RPM, 4-cycle, gasoline powered, electric start with charging system, low tone muffler system
Blower:	Positive displacement rotary type, Max. Air output: 5.7m ³ /min. Max. Air Pressure: .83 Bar Corrosion resistant Silencer Air-Filter
Drive:	Direct or optional (2) V-Belts
Control System:	0-70 liters/hr. using water. Stainless Steel Flow Meter with solution taps. Tank Pressure gauge, Spray ON/OFF, temperature gauge, night light and control valve. Remote control box with 5 meter extension cable.
Nozzle System:	Boom type, with "Double Twist" 360° vertical and horizontal rotation, Dual High-Output ULV Nozzles made from corrosion resistant metal.
Tanks:	38 liters (10 gal.)
Formulation:	Corrosion resistant Stainless Steel
Gasoline:	6 liters (1.58 gal.)
Flush:	3.8 liters (1 gal.)
Battery:	12 Volts DC (Mounted in battery box)
Particle Size:	Meets the label requirements of all currently. Available formulations by producing 90% or more of droplets under 20 microns.
Options:	Flush system, emergency flow meter by-pass valve, Machine Cover with Silkscreen, Sewer attachment, Tool Box

Machine Dimensions *uncrated* inches (cm)

Length	Width	Height
41" (104.1)	28" (71.1)	38" (96.5)

Shipping Dimensions *crated*

48" (122)	40" (102)	39" (99)
-----------	-----------	----------

Machine Weight: 298 lbs. (135 kg)

Shipping Weight: 415 lbs. (188 kg)

Shipping Volume (cube): 43.3 Cu. Ft. (1.23 Cu. m.)